Global Partner for Environmental Test Chambers



AGREE-Type Combined Temperature / Vibration Chambers

The EV Series AGREE style chambers are offered in various sizes and accommodate electro-dynamic, HALT/HASS mechanical vibration systems or roll-in product carts. The EV Series offers flexibility to be used as a test chamber with or without vibration tables.

Features:

- Engineered to adapt to all vibration tables in the market.
- Dual door design available for easy loading/unloading
- Gantry and Cantilever styles available for greater testing flexibility
- Easy access side panels
- Multiple door options available





Design & Performance

Model Number		EV40		EV70		EVH40		EVH81		
Airflow			Ce	ling		Rear-Wall				
Test Space Volume	Cubic Feet/Liters	40 / 1132		70 / 1982		40 / 1132		81 / 2300		
Test Space Dimensions	Width	44" (1118mm)		54" (1372mm)		44" (1118mm)		54" (1372mm)		
	Depth	44" (1118mm)		54" (1372mm)		44" (1118mm)		54" (1372mm)		
	Height	36" (914mm)		40" (1016mm)		36" (914mm)		48" (1219mm)		
Exterior Dimensions	Width	78" (1981mm)		78" (1980mm)		78" (1981mm)		78" (1980mm)		
	Depth	112" (2845mm)		117" (2972mm)		112" (2845mm)		130" (3300mm)		
	Height	96" (2440mm)		100" (2540mm)		96" (2440mm)		110" (2795mm)		
Temperature Change Rate ¹	Heating Rate	13°C/min	20°C/min	18°C/min	25°C/min	10°C/min	18°C/min	15°C/min	18°C/min	
	Cooling Rate	13°C/min	20°C/min	18°C/min	25°C/min	11°C/min	18°C/min	15°C/min	18°C/min	
Temperature Range ²	range ² Minimum -73°C (-99°F)									
	Maximum		+180°C (+356°F)							
Humidity Range			- 10%RH to 98%RH							

Gantry Option

 $Performances \ are \ based \ on \ laboratory \ conditions \ at +24^{\circ}C, 60\ Hz, with \ cooling \ water \ inlet \ temperature \ and \ flow \ rate \ according \ to \ requirements.$

Performances at 50 Hz may vary. Please consult with your local Sales Representative if your conditions vary

 $Temperature\ ramp\ rates\ are\ average,\ not\ linear\ rates\ of\ change.$ $^1Heating\ and\ cooling\ rates\ between\ +85^\circ C\ and\ -40^\circ C\ in\ an\ empty\ chamber;\ measured\ at\ the\ supply\ air\ and\ rates\ of\ change.$

² Temperature range is limited if export license is not granted, please consult with your local sales representative